

FANLESS HD^N



Described as one of the industry's most compelling new products, the Seneca Fanless HDn transforms the Intel® NUC into an industrial-grade, long-life media player optimized for digital signage and edge applications. Purpose-built for retail, hospitality, quick-serve restaurant and kiosk environments, the Fanless HDn boasts a solid-state, integrator-friendly design.

Unlike other manufacturers who ship one-size-fits-all solutions, Seneca experts carefully plan and pair you with the right media player, scalable to meet specific needs. Each system comes equipped with Seneca's Maestro software, which loads and optimizes your CMS or analytics applications, saving hours of integration and setup time.

Designed and developed by Seneca's Advanced Engineering Team, the new Fanless HDn was created in the world-class Seneca testing facilities designed by Intel®. From inception, Seneca systems are tested in real-world digital signage and edge environments to guarantee maximum reliability in mission-critical installations.

THE SENECA DIFFERENCE



Standard with all Seneca media players, Maestro gets your optimized system up and running in minutes instead of hours. We channeled years of value engineering into an intuitive dashboard that eliminates hundreds of keystrokes. You don't even need an internet connection or data transfer from external drives.

KEY FEATURES

- Solid-state with internal power
- Turnkey CMS integration
- All-aluminum chassis
- Advanced fin design
- Solid copper thermal component
- Dual HDMI 2.0



FANLESS HDn

FEATURES AND SPECIFICATIONS



Processor	Intel® Core™ i3 7100U (3M 2.4GHz) Intel® Core™ i5 vPro™ 7300U (4M 2.6GHz)
Operating System	Windows 10 IOT Enterprise, Linux
Memory	Up to 32GB DDR4 2133MHz 1.2V SO-DIMM Dual Channel
Storage	Up to 2TBM.2
LAN	1 x Intel® i219-LM 10/100/1000
USB	Front: 2 x USB 3.0 ; Rear: 2 x USB 3.0
Video Output	2 x HDMI 2.0a (1 w/ CEC)
Wireless	Intel® Wireless-AC 8265 802.11ac 2x2
Dimension	7.5" x 2" x 4.3"
Playback	1x 2160p / 60fps; 2x 2160p / 30fps; 2x 1080p / 60fps
Weight	2.8lbs
VESA/Wall	75mm / 100mm
Power	100-240VAC
Safety & Emissions	UL, CE, FCC, CB
Included	1 x Power; 1 x Fanless HDn; 1x Tool-less VESA
Warranty	39 month
Operating Temperature	40°C (at full system utilization)

