

Scribe

Panopto Video Appliance



The Seneca Scribe is an exclusive video capture offering co-developed with Panopto that can be installed anywhere, including A/V racks, desktops and podiums. With optimized system resources and balanced drivers, this solution guarantees smooth integration and reliability you can depend on.

Designed and developed by Arrow's Advanced Engineering Team, the Scribe was created in the world-class testing facilities with our industry knowledge and hardware expertise. From inception, Seneca systems are tested in real-world environments to guarantee maximum reliability in mission-critical installations.

Features

- **Dual HDMI, Quad HDMI, Dual SDI, or Quad SDI video capture card options**
- **Powered by the 10th generation Intel® Core™ processors**
- **Quiet and cool design for low noise threshold during recording and component stability**
- **Co-developed and certified with Panopto, an industry-leading lecture capture ISV**
- **Designed for use in distance learning as well as distance medicine, lecture capture, boardrooms, courtrooms and other environments**
- **Stream HTML 5 video to any device using HLS streaming format**
- **Schedule recordings and live webcasts in advance**



Scribe

Features and Specifications (GPS-01-V1)

System

Processor	10th Generation Intel® Core™ Processor
Operating System	Windows 10 IoT LTSC
Manufacturer	Seneca®
Graphics	Intel® UHD Graphics 630
Video Output	HDMI and Display Port
Capture	Dual HDMI, Quad HDMI, Dual SDI, Quad SDI
Storage	1 TB HDD
Memory	16 GB DDR4 3200MHz
Connectivity	2 x Intel® LAN
USB	4 x USB 3.1 (Rear)
Expandability	2 x LAN (RJ-45) 2 x Serial (RS-232) 2 x Display Ports 1 x HDMI 1 x Line Out 1 x Mic In
Warranty	3-Year Hot-Spare (5 year option)

Mechanicals

Power Supply	300 W High Efficiency Low Noise PSU
Thermals	50° C (122° F) Max at full CPU utilization
Cooling	2 x 40 mm low noise fans
Operating Temperature	0 ~ 50° C (32 ~ 122° F)
Storage Temperature	-20 ~ 80° C (-4 ~ 176° F)
Operating Humidity	5 ~ 90% Relative Humidity, Non-Condensing
Storage Humidity	0 ~ 90% Relative Humidity, Non-Condensing
Dimensions (w x h x d)	17.25 x 1.75 x 12.75 inches / 438 x 45 x 324 millimeters (without handles) 19 x 1.75 x 12.75 inches / 483 x 45 x 324 millimeters (with handles)
Weight	11 lbs / 5 kg (System) 14 lbs / 6.4 kg (Shipping)

